

## Szilikon gumitömlők



Hajtástechnika<sup>Kft.</sup>

Belső átmérő	Külső átmérő	Falvastagság	Tömeg	Cikkszám
mm	mm	mm	g / fm	
2	4	1,0	18,0	SZ TOML 2 4
3	5	1,0	25,0	SZ TOML 3 5
3	6	1,5	35,0	SZ TOML 3 6
3	9	3,0	42,0	SZ TOML 3 9
4	6	1,0	39,0	SZ TOML 4 6
4	7	1,5	51,0	SZ TOML 4 7
5	7	1,0	48,0	SZ TOML 5 7
5	8	1,5	55,0	SZ TOML 5 8
6	8	1,0	53,0	SZ TOML 6 8
6	9	1,5	60,0	SZ TOML 6 9
8	10	1,0	63,0	SZ TOML 8 10
8	12	2,0	66,0	SZ TOML 8 12
8	14	3,0	69,0	SZ TOML 8 14
8	16	4,0	75,0	SZ TOML 8 16
10	14	2,0	68,0	SZ TOML 10 14
10	15	2,5	73,0	SZ TOML 10 15
10	16	3,0	79,0	SZ TOML 10 16
12	14	1,0	87,0	SZ TOML 12 14
12	16	2,0	98,0	SZ TOML 12 16
15	19	2,0	110,0	SZ TOML 15 19
15	21	3,0	140,0	SZ TOML 15 21
18	24	3,0	260,0	SZ TOML 18 24
26	32	3,0	320,0	SZ TOML 26 32
30	38	4,0	450,0	SZ TOML 30 38
32	45	6,5	480,0	SZ TOML 32 45